

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number
WO 2005/041451 A1

(51) International Patent Classification⁷: **H04B 10/17**,
H04J 14/02

(21) International Application Number:
PCT/EP2004/052641

(22) International Filing Date: 22 October 2004 (22.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
103 49 891.5 25 October 2003 (25.10.2003) DE

(71) Applicant (for all designated States except US): **MAR-
CONI COMMUNICATIONS GMBH [DE/DE]**; Gerber-
strasse 33, 71520 Backnang (DE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **PEGG, Steven**
[GB/GB]; 2 Henry Bird Court, Northampton Northamp-
tonshire NN4 8GF (GB).

(74) Agents: **COCKAYNE, Gillian et al.**; Marconi Intellec-
tual Property, Crompton Close, Basildon Essex SS14 3BA
(GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: OPTICAL NETWORK AND AMPLIFIER NODE THEREFORE



(57) Abstract: An optical network comprises a transmitter node (1), a receiver node (4) and an optical fibre (3) for transmitting an optical wavelength-division multiplex signal having payload channels and a supervisory channel between the nodes (1, 4). At least one of the nodes has an amplifier (8, 13) which is passed by the multiplex signal. The transmitter node (1) has a source (11) for the supervisory channel and a multiplexer (12) for combining the payload channels and the supervisory channel in order to form the optical wavelength-division multiplex signal, and the receiver node (4) has a sink (16) for the supervisory channel and a demultiplexer (14) for separating the wavelength-division multiplex signal into supervisory and the payload channels. The multiplexer (12) and the demultiplexer (14) are adapted to insert and extract, respectively, as the supervisory channel, a wavelength into/from the optical multiplex signal, the attenuation of which between source (11) and sink (16) is essentially the same in the pumped and unpumped states of the amplifier (8, 13).